


EMVA 1288 Data Sheet m0802

This datasheet describes the specification according to the standard 1288 release 3.1 for "Characterization and Presentation of Specification Data for Image Sensors and Cameras" issued on December 30, 2016 by the European Machine Vision Association (EMVA), published at www.standard1288.org and the *zenodo EMVA 1288 community* with proprietary extensions from AEON. The measurements were performed with the AEON ACC3 Release 6, 26.11.2016, SN 0005(MatrixVision.

Measurements performed by T.Renner, Matrix Vision GmbH

Vendor	MATRIX VI-SION	Type of data presented	Single
Model	mvBlueCOUGAR-XD107bG	Operation point 1 (page 3)	
Serial number	GX210724	Wavelength centroid	535.0 nm
Sensor diagonal	17.55 mm	Wavelength FWHM	31.0 nm
Lens category	C-Mount	Gain, black-level	0dB, 0.1
Resolution	3216 × 2208, 12 bit	Optional data measured	
Pixel size (h×v)	4.50 μm × 4.50 μm	None	
Sensor	IMX428		
Sensor type	CMOS		
Shutter type	Global		
Overlap cap.	Overlapping		
Max. frame rate	16.8 Hz		
Interface type	GigE Vision		




Summary Sheet for Operation Point 1 at a Wavelength of 535 nm

Type of data	Single	Gain, black-level	0dB, 0.1
Exposure control	By irradiance	Environmental temperature	25.1°C
Exposure time	18.00 ms	Camera body temperature	38.4°C
Frame rate	16.0 Hz	Internal temperature(s)	—
Data transfer mode	Mono12	Wavelength, centr., FWHM	535 nm, 31.0 nm


Photon Transfer

Photon transfer m0802, 535 nm, 02.05.2019



Signal-to-Noise Ratio

SNR m0802, 535 nm, 02.05.2019



Quantum efficiency

η 69.8%

Overall system gain

K 0.162 DN/e⁻

$1/K$ 6.189 e⁻/DN

Temporal dark noise

σ_d 5.58 e⁻

$\sigma_{y.dark}$ 0.95 DN

Signal-to-noise ratio

SNR_{max} 157

43.9 dB

7.3 bit

$1/\text{SNR}_{max}$ 0.64 %

Absolute sensitivity threshold

$\mu_{p.min}$ 9.14 p

$\mu_{p.min.area}$ 0.451 p/ μm^2

$\mu_{e.min}$ 6.38 e⁻

$\mu_{e.min.area}$ 0.315 e⁻/ μm^2

Saturation capacity

$\mu_{p.sat}$ 35318 p

$\mu_{p.sat.area}$ 1744 p/ μm^2

$\mu_{e.sat}$ 24664 e⁻

$\mu_{e.sat.area}$ 1218 e⁻/ μm^2

Dynamic range

DR 3864

71.7 dB

11.9 bit

Spatial nonuniformities

DSNU₁₂₈₈ 1.07 e⁻

0.17 DN

PRNU₁₂₈₈ 0.81 %

Linearity error

LE_{min} -0.24%

LE_{max} 0.77%

Dark current

$\mu_{c.mean}$ -20.5 ± 6.2 e⁻/s

-3.31 DN/s

$\mu_{c.var}$ 6.2 ± 1.4 e⁻/s

T_d — °C